

**SPBEL118**

Design by Manuel Vivian

Collection consisting of suspended lamps with a metal frame covered with strips of extra smooth flame-retardant pongé fabric. Available in several colours and sizes.


Typology: SUSPENDED

Ratings

- Built in **LED** module
- CCT 3000 K
- Downlight and uplight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable DALI LED driver
- Steel frame
- Opalescent diffuser

SP BEL 118 LED

BELL / diffusore INCLUSO, con illuminazione verso alto e basso / diffuser INCLUDED, with upward and downward lighting



Type	Article	Colours	Finish	Source
SP	BEL 118 LED	BC white	XX	LED 98W - diffused beam 3000K*, 4000K
		BW warm white		
		GI gold yellow		
		NE black		
		RS red		

CE IP20 CRI90 **LED** ~10719 lm* 109 lm/W* 110-240Vac
example composition code SP BEL118LED RS XX

Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,59	1,03	1,37	1,84	2,34	2,67	3,31	1,88	1,85

Available colors

BC
WhiteBW
Warm whiteGI
Gold yellowNE
BlackRS
Red

Altri colori disponibili su richiesta / Other colors available upon request.

E

SPBEL118LED _ _ XX

CUSTOMER _____ NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.