



**SPBEL118**  
Design by Manuel Vivian

Collection consisting of suspended lamps with a metal frame covered with strips of extra smooth flame-retardant pongé fabric. Available in several colours and sizes.

Typology: SUSPENDED


Ratings

- Built in **LED** module
- CCT 3000 K
- Downlight and uplight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable DALI LED driver
- Steel frame
- Opalescent diffuser

Product code composition

**BELL** / diffusore INCLUSO, con illuminazione verso alto e basso / *diffuser INCLUDED, with upward and downward lighting*

Type	Article	Colours	Finish	Source
SP	BEL 118 LED	BC white BL electric blue BW warm white GI gold yellow MA brown MT brick red NE black RB burgundy RS red VE green	XX	LED 98W - diffused beam 3000K*, 4000K



CE IP20 CRI90 **LED** ~10719 lm\* 109 lm/W\* 110-240VAC  
example composition code SP BEL118LED RS XX

Available colors



EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

SPBEL118LED \_ \_ XX

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.