

**PLUL1090**  
**PLUL2090**  
 Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.  
 Available in several colours and sizes.  
 Available with sound absorbing panel option.

Typology: WALL, CEILING


**Ratings**

- Built in **LED** module
- CCT 3000 K or 2700K
- Wallward light (wall), downlight or uplight (ceiling)
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser


Product code composition

PL UL 1: kg 5.8 m3 0.128  
 PL UL 2: kg 6.3 m3 0.128


U-LIGHT / h10 cm or h25 cm ceiling lamp with canopy / DRIVER INCLUDED /



Type	Article	Colours	Version	Source
PL	UL 1 090 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 63W - diffused beam 3000K*, 2700K other CCT options available upon request
	UL 2 090 LED (h25 cm)	RU rust brown		



altezze disponibili  
available heights



CE IP20 CRI90 **LED** ~4904 lm\* 78 lm/W\* 100-240VAc

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).  
 Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code PL UL2090LED AN XX

-sound absorbing option upon request- for more information see [www.axolight.eu/u-light/u-light-sound-absorbing.pdf](http://www.axolight.eu/u-light/u-light-sound-absorbing.pdf)

Available colors



AN  
Anthracite grey

RU  
Rust brown

Sound absorbing option upon request

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

PLUL \_ 090LED \_ \_ XX

\_\_\_\_\_

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.  
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.