

PLUL1090
PLUL2090
Design by Timo Ripatti



Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.
Available with sound absorbing panel option.

Typology: WALL, CEILING


Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Wallward light (wall), downlight or uplight (ceiling)
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

PL UL 1: kg 5.8 m3 0.128
PL UL 2: kg 6.3 m3 0.128



altezze disponibili
available heights



Product code composition

U-LIGHT / h10 cm or h25 cm ceiling lamp with canopy / DRIVER INCLUDED /

Type	Article	Colours	Version	Source
PL	UL 1 090 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 63W - diffused beam 3000K*, 2700K other CCT options available upon request
	UL 2 090 LED (h25 cm)	RU rust brown		

CE IP20 CRI90 **LED** ~4904 lm* 78 lm/W* 100-240VAc

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).
Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code PL UL2090LED AN XX

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf

Available colors



AN
Anthracite
grey



RU
Rust brown



Sound
absorbing
option upon
request

CUSTOMER _____ NOTES _____

PLUL _ 090LED _ _ XX

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.