
PLUL1120
PLUL2120

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.

Available in several colours and sizes.


Available with sound absorbing panel option.

Typology: WALL, CEILING LAMP



Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Wallward light (wall), downlight or uplight (ceiling)
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

PL UL 1: kg 6.6 m3 0.180
PL UL 2: kg 7 m3 0.180

standard
canopy
Ø 33cm


rosone standard / standard canopy


altezze disponibili
available heights

10 cm
height

25 cm
height

Product code composition

U-LIGHT / h10cm or h25cm ceiling lamp with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
PL	UL 1120 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 86W - diffused beam 3000K*, 2700K other CCT options available upon request
	UL 2120 LED (h25 cm)	RU rust brown		



IP20

CRI90



~7354 lm*

86 lm/W*

100-240VAC

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).
Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code PL UL1120LED RU XX

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf

Available colors


AN
Anthracite
grey

RU
Rust brown

Sound
absorbing
option upon
request

CUSTOMER _____

NOTES _____

PLUL _ 120LED _ _ XX

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.