



**SP LIAI G 1**

Design by Sara Moroni

Collection consisting of metal suspended lamps. Available in several colours and sizes. Built-in dimmable LED light source.

Typology: suspended

**Ratings**


- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable 0/1-10V

**SP LIA G 1I (RECESSED)**

kg 2,2 m³ 0,16

Product code composition

LIAISON / DRIVER NOT INCLUDED



Type	Article	Arch / Final & sphere finishes	Led source
SP	LIA G 1I	NE black / NE black	LED 6,6W - optic ~ 40° beam 3000K* 2700K upon request
		NE black / OO matt gold	
		OO matt gold / NE black	

CE IP20 CRI>90  **LED** 700mA - 9,4Vdc ~671 lm\* ~102 lm/W\*

example composition code SP LIA G 1I NE NE LED

optional accessories for recessed versions . See page 154

Compatible with pivot system  
pag.76 

Available colors



NE/OT  
Black/brass

OT/NE  
Brass/black

SA/NE  
Sand/black

SPLIAG1I\_ \_ \_ \_ LED

CUSTOMER \_\_\_\_\_

NOTES \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.