

**SP LIAI G 2**

Design by Sara Moroni

Collection consisting of metal suspended lamps.
Available in several colours and sizes.
Built-in dimmable LED light source.


Typology: suspended

Ratings

- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable 0/1-10V

SP LIAI G 2

kg 2,734 m³ 0,16



Product code composition

LIAISON / DRIVER INCLUDED

| Type | Article | Arch / Final & sphere finishes | Source |
|------|----------|--------------------------------|---|
| SP | LIAI G 2 | NE black / NE black | LED 2 x 6,6W - optic ~ 40° beam 3000K* 2700K upon request |
| | | NE black / OO matt gold | |
| | | OO matt gold / NE black | |

IP20 CRI>90 **LED** ~1342 lm* ~102 lm/W* 220-240VAc

example composition code SP LIAI G 2 OO NE LED

Available colors

NE/NE
Black/blackOO/NE
Matt gold
/blackNE/OO
Black/ Matt
gold

Customizable

SP LIAI G 2 _ _ _ _ LED

CUSTOMER _____ NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.