



### SP ULA 090

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.  
Available in several colours and sizes.  
Available with sound absorbing panel option.


Typology: SUSPENDED LAMP

### Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight or uplight
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

### Product code composition

kg 5.8 m3 0.128



rosone standard /standard canopy



U-LIGHT / suspension with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
SP	ULA 090 LED	AN anthracite grey RU rust brown	XX standard canopy	LED 63W - diffused beam 3000K*, 2700K other CCT options available upon request



IP20

CRI90



**LED**

~4904 lm\* 78 lm/W\*

100-240VAC

-sound absorbing option upon request- for more information see [www.axolight.eu/u-light/u-light-sound-absorbing.pdf](http://www.axolight.eu/u-light/u-light-sound-absorbing.pdf)

### Available colors



AN  
Anthracite  
grey



RU  
Rust brown



Sound  
absorbing  
option upon  
request

SPULA090LED \_ \_ XX

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.