
**SPULA090 - recessed**

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.

Available in several colours and sizes.

Available with sound absorbing panel option.

Typology: SUSPENDED LAMP

**Ratings**



- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight or uplight
- Surface installation over holes (cable grippers) and in ceiling cut-out (recessed canopy)
- Supply voltage 24VDC
- Switch mode: on-off
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

kg 2.5 m3 0.126

Product code composition

**U-LIGHT** / recessed suspension lamp / DRIVER NOT INCLUDED

Type	Article	Colours	Version	Source
SP	ULA 090 LED	AN anthracite grey RU rust brown	IN recessed canopy	LED 54W - diffused beam <b>3000K*, 2700K</b> 24VDC other CCT options available upon request


**rosone incasso / recessed canopy**

CE III IP20 CRI90 **LED** ~4904 lm\* 91 lm/W\* 24Vdc

foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

example composition code SP ULA090LED AN IN

-for optional drivers or dimming technology please refer to our pricelist or contact our representatives

-sound absorbing option upon request- for more information see [www.axolight.eu/u-light/u-light-sound-absorbing.pdf](http://www.axolight.eu/u-light/u-light-sound-absorbing.pdf)

Available colors


**AN**  
Anthracite  
grey

**RU**  
Rust brown

Sound  
absorbing  
option upon  
request

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

SPULA090LED \_ \_ IN

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.