

**SPULA160 - recessed**  
Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.  
Available in several colours and sizes.  
Available with sound absorbing panel option.

Typology: SUSPENDED LAMP


**Ratings**

- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight or uplight
- Surface installation over holes (cable grippers) and in ceiling cut-out (recessed canopy)
- Supply voltage 24VDC
- Switch mode: on-off
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

kg 4.8 m3 0.280

Product code composition

U-LIGHT / recessed suspension lamp / DRIVER NOT INCLUDED



Type	Article	Colours	Version	Source
SP	ULA 160 LED	AN anthracite grey RU rust brown	IN recessed canopy	LED 102W - diffused beam 3000K*, 2700K 24VDC other CCT options available upon request

CE III IP20 CRI90  **LED** ~8575 lm\* 84 lm/W\* 24Vdc


foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

example composition code SP ULA160LED AN IN

-for optional drivers or dimming technology please refer to our pricelist or contact our representatives

-sound absorbing option upon request- for more information see [www.axolight.eu/u-light/u-light-sound-absorbing.pdf](http://www.axolight.eu/u-light/u-light-sound-absorbing.pdf)

rosone incasso / recessed canopy



Available colors



AN  
Anthracite  
grey

RU  
Rust brown

Sound  
absorbing  
option upon  
request

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

SPULA160LED \_ \_ IN

\_\_\_\_\_

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.