

SPSKR150
Design by Manuel Vivian

Collection of ceiling, suspended and table lamps in flame-retardant TREVIRA®CS fabric (100% polyester Glow wire 960 °C), available in several sizes and colours. The fabric can also come in a double-layer version with an exterior black net fabric.

Typology: SUSPENDED


Ratings

- E27
- Downlight and uplight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Steel frame, painted
- Cone in pongé fabric and light covering in jersey

kg 19 m³ 2.54

Product code composition

SKIRT / diffuser INCLUDED, with upward and downward lighting



Type	Article	Exterior Net	Fabric Colours	Source
SP	SKR 150 E27	NE black net	BC white	E27 4xMax 16W + 1xMax 12W LED or 5xMax 23W fluo or 4xMax 70W + 1xMax 57W halo
		XX no black net	AR orange	
			AZ light blue	
			BL blue	
			FU fuchsia	
			GR light grey	
			MA brown	
			RS red	
			VE light green	

SINGLE FABRIC
Fireproof class I= C1, GB= CRIB 5, D=B1, F= M1,
EN= 102/1-2, A 652 / Weight 340 ± 5% gr/m² /
Abrasion resistance (Martindale): 40.000 ± 10% rubs /
Pilling Grade 5 / Light fastness grade 6

BLACK NET FINISH FABRIC
Fireproof class I= C1, F= M1, D= B1 DIN 4102 /
Weight 214 ± 5% gr/m² / Abrasion resistance
(Martindale): 30.000 ± 10% rubs / Pilling Grade 5 /
Light fastness grade 5

CE IP20 +LED

example composition code | SP | SKR150E27 | XX | BC |

For optional accessories please refer to our pricelist, website or contact our representatives

Available colors



BC White AR Orange AZ Light blue BL Blue FU Fuchsia GR Light grey MA Brown RS Red VE Light green



Black net over a white fabric NEBC

EELc (Energy Efficiency Label compatibility): E, D, C, B, A, A+

SPSKR150E27_ _ _ _

CUSTOMER _____

NOTES _____

NOTICE:
Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.