



SPVEL160 Design by Manuel Vivian

Collection of suspended lamps. The radial diffuser and light covering are treated with a flame-retardant (Glow wire 960 °C and 750°C respectively). Available in several colours and sizes.

Typology: SUSPENDED

Ratings


- Built in **LED** module
- CCT 3000 K
- Downlight and uplight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable DALI LED driver
- Steel frame, painted
- Radial cone diffuser in pongé fabric and light covering in jersey

Product code composition

VELVET / diffuser INCLUDED, with upward and downward lighting / DRIVER INCLUDED

Type	Article	Colours (lampshade)	Colour (Radial diffuser)	Source
SP	VEL 160 LED	BC ice white	BC white	LED 98W - diffused beam 3000K available on request 4000K
		AR orange	BL electric blue	
		AZ light blue	BW warm white	
		BA ivory white	GI gold yellow	
		BL blue	MA brown	
		MA brown	MT brick red	
		NE black	NE black	
		RB burgundy	RB burgundy	
			RS red	
			VE green	

kg 25 m³ 4.32




Micro 2000 flame retardant fabric 80% polyester + 20% cotton
Fleece finishing 100% polyester
Weight 276 ± 5% gr/m²
Abrasion resistance (Martindale) 25.000 ± 10% rubs
Pilling grade 4/5
Light fastness grade 4/5 + self-extinguishing PVC
Glow wire 750 °C

CE IP20 CRI90 LED ~10719 lm 109 lm/W 110-240VAC

example composition code | SP | VEL160LED | MA | BC |

Available lampshade colors



BC Ice white AR Orange AZ Light blue BA Ivory white BL Blue MA Brown NE Black RB Burgundy

Available radial diffuser colors



BC White BL Electric blue BW Warm white GI Gold yellow MA Brown MT Brick red NE Black RB Burgundy RS RED VE Green

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

SPVEL160LED_ _ _ _

CUSTOMER _____

NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.