

SPULA120 - recessed

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.
Available with sound absorbing panel option.

Typology: SUSPENDED LAMP


Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight or uplight
- Surface installation over holes (cable grippers) and in ceiling cut-out (recessed canopy)
- Supply voltage 24Vdc
- Switch mode: on-off
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

recessed kg 3 m3 0.150

Product code composition

U-LIGHT / recessed suspension lamp / DRIVER NOT INCLUDED



Type	Article	Colours	Version	Source
SP	ULA 120 LED	AN anthracite grey RU rust brown	IN recessed canopy	LED 74W - diffused beam 3000K*, 2700K 24VDC other CCT options available upon request

~7354 lm* 99 lm/W* 24Vdc

foro - hole \varnothing 4,5 cm / profondità min - min depth 10 cm

example composition code **SP ULA120LED RU IN**

-for optional drivers or dimming technology please refer to our pricelist or contact our representatives

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf

Available colors



AN
Anthracite grey

RU
Rust brown

Sound absorbing option upon request

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____

SPULA120LED _ _ IN

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.