

SP ULA 180
Design by Timo Ripatti


Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.
Available with sound absorbing panel option.

Typology: SUSPENDED LAMP

Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight or uplight
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

kg 10,5 m3 0,330 Product code composition



U-LIGHT / suspension with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
SP	ULA 180 LED	AN anthracite grey RU rust brown	XX standard canopy	LED 153W - diffused beam 3000K*, 2700K other CCT options available upon request

CE IP20 CRI90 **LED** ~9800 lm* 64 lm/W* 100-240Vac

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf

rosone standard /standard canopy



Available colors



AN
Anthracite
grey

RU
Rust brown

Sound
absorbing
option upon
request

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

SPULA180LED _ _ XX CUSTOMER _____ NOTES _____

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.