



E 2 100 1 0X 1 X
Design by Manuel Vivian

Aluminium suspended lamp, also in a recessed version. Available in black or white. Built-in LED light source.

Typology: SUSPENSION LAMP

Ratings

- Built in **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Aluminium pendant, painted
- Reflector and closing glass

kg 1.07 m³ 0.0073

Product code composition

STILLA / LED 8,7W / DRIVER INCLUDED



Zone	Type	Article	System compatibility	Finish	LED colour temperature	Beam options
E	2	100	1 monopoint canopy version	04 matt black	1 3000 K	2 47° ~688lm
				07 white 9016		3 60° ~668lm

CE IP20 CRI80 **LED** 79lm/W (47° beam) - 76lm/W (60° beam)

example composition code | E | 2 | 100 | 1 | 07 | 1 | 2

for optional accessories please refer to our pricelist or contact our representatives

Available colors



04
Matt black



07
White RAL 9016

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

E210010_1_

CUSTOMER _____

NOTES _____

NOTICE:
Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.