

**SPULI090**

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.
Available with sound absorbing panel option.

Typology: SUSPENDED LAMP


Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x23 mm
- Opalescent diffuser


Product code composition

kg 7.2 m3 0.19

U-LIGHT / downward lighting only / DRIVER INCLUDED



Type	Article	Colours	Code End	Source
SP	ULI 090 LED	AN anthracite grey RU rust brown	XX	LED 63W – diffused beam 3000K*, 2700K other CCT options available upon request



IP20 CRI90

**LED**

~4904 lm* 78 lm/W*

100-240VAC

example composition code SP ULI090LED RU XX

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf

Available colors

AN
Anthracite
greyRU
Rust brownSound
absorbing
option upon
request

SPULI090LED _ _ XX

CUSTOMER _____

NOTES _____

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.