


SPULI120

Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.

Available in several colours and sizes.

Available with sound absorbing panel option.


Typology: SUSPENDED

Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Downlight
- Surface installation over holes
- Supply voltage ~100-240VAC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

Product code composition
U-LIGHT / downward lighting only / DRIVER INCLUDED

kg 8.2 m3 0.33



Type	Article	Colours	Code End	Source
SP	ULI 120 LED	AN anthracite grey RU rust brown	XX	LED 86W - diffused beam 3000K*, 2700K other CCT options available upon request



IP20 CRI90



~7354 lm* 86 lm/W*

100-240VAC

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf
Available colors

AN
Anthracite
grey

RU
Rust brown

Sound
absorbing
option upon
request

SPULI120LED _ _ XX

CUSTOMER _____

NOTES _____

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.