

**SP LIAD P 2**

Design by Sara Moroni

Collection consisting of metal suspended lamps.
Available in several colours and sizes.
Built-in dimmable LED light source.


Typology: suspended

Ratings

- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable 0/1-10V

SP LIAD P 2

kg 3,678 m³ 0,0759



Product code composition

LIAISON / DRIVER INCLUDED

Type	Article	Arch / Final & sphere finishes	Source
SP	LIAD P 2	NE black / NE black	LED 2 x 6,6W - optic ~ 40° beam 3000K* 2700K upon request
		NE black / OO matt gold	
		OO matt gold / NE black	

IP20 CRI>90 **LED** ~1342 lm* ~102 lm/W* 220-240VAc

example composition code SP LIAD P 2 NE NE LED

Available colors

NE/NE
Black/blackOO/NE
Matt gold
/blackNE/OO
Black/ Matt
gold

Customizable

SPLIADP2_ _ _ _ LED

CUSTOMER _____

NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.