**PLPIVO**

Design by Ryosuke Fukusada

Collection consisting of modular ceiling - wall lamps.  
Available in different colors, beam and CCT

Typology: CEILING / WALL LAMP


## Ratings

- Built in **LED** module
- CCT 3000 K\* 2700 K 3500 K
- Optic ~12° or ~38° beam
- Surface installation over holes
- Supply voltage 220-240Vac
- Switch mode: on-off
- Aluminum body




## PIVOT / DRIVER INCLUDED (DIMMABLE)

| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 02           | 1 12° | 1 2700K  | BC white  | 035 | 2 X 6,5W<br>lm: 1342*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



## PIVOT / DRIVER INCLUDED (DIMMABLE)


| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 03           | 1 12° | 1 2700K  | BC white  | 035 | 3 X 6,5W<br>lm: 2013*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



## PIVOT / DRIVER INCLUDED (DIMMABLE)


| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 04           | 1 12° | 1 2700K  | BC white  | 035 | 4 X 6,5W<br>lm: 2684*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |

IP20 CRI90
 
 220-240VAC **LED**  
 example composition code PL PIVO 04 32 BC 065




PIVOT / DRIVER INCLUDED (DIMMABLE)

| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 05           | 1 12° | 1 2700K  | BC white  | 035 | 5 X 6,5W<br>lm: 3355*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



PIVOT / DRIVER INCLUDED (DIMMABLE)

| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 06           | 1 12° | 1 2700K  | BC white  | 035 | 6 X 6,5W<br>lm: 4076*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



PIVOT / DRIVER INCLUDED (DIMMABLE)


| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 07           | 1 12° | 1 2700K  | BC white  | 035 | 7 X 6,5W<br>lm: 4697*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



IP20 CRI90


dimming  
0/1-10V220-240V<sub>AC</sub> LED

example composition code PL PIVO 07 32 BC 065




PIVOT / DRIVER INCLUDED (DIMMABLE)

| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 08           | 1 12° | 1 2700K  | BC white  | 035 | 8 X 6,5W<br>lm: 5368*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



PIVOT / DRIVER INCLUDED (DIMMABLE)

| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                        |
|------|---------|--------------|-------|----------|-----------|-----|-------------------------------------|
| PL   | PIVO    | 09           | 1 12° | 1 2700K  | BC white  | 035 | 9 X 6,5W<br>lm: 6039*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                     |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                     |



PIVOT / DRIVER INCLUDED (DIMMABLE)

| Type | Article | Light number | Beam  | CCT      | Colours   | Rod | LED - Source                         |
|------|---------|--------------|-------|----------|-----------|-----|--------------------------------------|
| PL   | PIVO    | 10           | 1 12° | 1 2700K  | BC white  | 035 | 10 X 6,5W<br>lm: 6710*<br>lm/w: 103* |
|      |         |              | 3 38° | 2 3000K* | NE black  | 065 |                                      |
|      |         |              |       | 3 3500K  | GE greige | 100 |                                      |



IP20 CRI90

220-240V<sub>AC</sub> LED

example composition code PL PIVO 10 32 BC 065

## Available colors

BC  
white

PLPIVOXXXXBCXXX

NE  
black

PLPIVOXXXXNEXXX

GE  
greige

PLPIVOXXXXGEXXX

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

PLPIVO \_ \_ \_ \_ \_


Luminous flux for all LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.

## Pivot Accessori / Accessories

### CANOPY

kg 1.25




CANOPY WITH SPINNING DEVICES / DRIVER NOT INCLUDED

| Code        | Colours   |    |
|-------------|-----------|----|
| ROSONEPIVOT | BC white  | XX |
|             | NE black  |    |
|             | GE greige |    |

example composition code ROSONEPIVOT BC XX

### SPOTLIGHT

kg 0.574



SPOTLIGHT SATELLITE / DRIVER NOT INCLUDED

| Code        | Beam  | CCT      | Colours   | LED - Source                       |
|-------------|-------|----------|-----------|------------------------------------|
| SATELLPIVOT | 1 12° | 1 2700K  | BC white  | 1 X 6,5W<br>lm: 671*<br>lm/w: 103* |
|             | 3 38° | 2 3000K* | NE black  |                                    |
|             |       | 3 3500K  | GE greige |                                    |



CRI90




LED 700mA - 9,2 Vdc

example composition code SATELLPIVOT 1 1 BC

### SPOTLIGHT X

kg 0.547



ORIENTABLE SPOTLIGHT SATELLITE / DRIVER NOT INCLUDED / COMPATIBLE ONLY WITH PENDANTS SATELLITE

| Code        | Beam  | CCT      | Colours   | LED - Source                       |
|-------------|-------|----------|-----------|------------------------------------|
| SATELTURNXX | 1 12° | 1 2700K  | BC white  | 1 X 6,5W<br>lm: 671*<br>lm/w: 103* |
|             | 3 38° | 2 3000K* | NE black  |                                    |
|             |       | 3 3500K  | GE greige |                                    |



CRI90




LED 700mA - 9,2 Vdc

example composition code SATELTURNXX 1 1 BC

## Pivot Accessori / Accessories

### PENDANTS

kg 0.240



PENDANTS SATELLITE / DRIVER NOT INCLUDED

Code

PENDANTSATELL

Colours

BC white

NE black

GE greige

example composition code PENDANTSATELL BC

### ROD 35 CM

kg 0.38



PIVOT / ROD 35 cm

Code

KITPIVOT035

Colours

BC white

NE black


GE greige

XX

example composition code KITPIVOT035 BC XX

### ROD 65 CM

kg 0.68



PIVOT / ROD 65 cm

Code

KITPIVOT065

Colours

BC white

NE black

GE greige

XX

example composition code KITPIVOT065 BC XX

### ROD 100 CM

kg 1.00



PIVOT / ROD 100 cm

Code

KITPIVOT100

Colours

BC white

NE black


GE greige

XX

example composition code KITPIVOT100 BC XX

## Pivot Accessori / Accessories

### JUNCTION KIT



#### PIVOT / JUNCTION KIT

##### Code

KITJUNCTIPPIV

KITJUNCTIGPIV


##### Colours

BC white

NE black

example composition code KITJUNCTIGPIV BC

### DIMMABLE 1 - 10V



#### DRIVER 700mA DIMMABLE 1 - 10V & PUSH


| Code        | Product                       | W Max | Input                | Output                   | Weight       |
|-------------|-------------------------------|-------|----------------------|--------------------------|--------------|
| CEDLTC00128 | Dimmable<br>0/1 - 10V<br>Push | 37    | 110-240V<br>50-60 Hz | 700mA constant<br>53 Vdc | net kg 0,215 |



IP20



#### Available colors

BC  
white

PLPIVOXXXXBCXXX

NE  
black

PLPIVOXXXXNEXXX

GE  
greige

PLPIVOXXXXGEXXX

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

Luminous flux for all LED luminaires is shown at source level.  
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.