



24VDC track for surface or suspended installation

The system includes a wide range of accessories that allow the coupling of several electrified tracks.

Color

White





Black





Code Construction


TRACK24TK X X XXXX



Load schemes




Accessories




TRACK24TK011 XXX
White
TRACK24TK015 XXX
Black

Live-end




TRACK24TK021 XXX
White
TRACK24TK025 XXX
Black

Electrical straight joint




TRACK24TK091 XXX
White
TRACK24TK095 XXX
Black

Mechanical straight joint



TRACK24TK031 XXX
White
TRACK24TK035 XXX
Black

Electrical L joint




TRACK24TK041 XXX
White
TRACK24TK045 XXX
Black

Mechanical L joint




TRACK24TK051 XXX
White
TRACK24TK055 XXX
Black

Dead end




TRACK24TK061 XXX
White
TRACK24TK065 XXX
Black

Track cover 300 cm



TRACK24TK-K01 XX
Suspension kit with
steel wire 200 cm and
automatic locking device




TRACK24TK10 XXXX
Reinforcing bracket for
linear junction


Drivers

24VDC		Hole mm
CEDLTC00136	On/off IP20 - Max 20W	Ø 60
CEDLTC00137	On/off IP20 - Max 70W	Ø 70
CEDLTC00138	On/off IP20 - Max 150W	Ø 80
CEDALV00001	Dimmable IP20, PUSH, DALI2, 0/1-10V - Max 24W	Ø 45
CEDKGP00001	Dimmable IP20, PUSH, DALI 2 - Max 100W	Ø 70

Lighting elements



MARK T6
6W - 24VDC




MARK T10
10W - 24VDC




JEWEL T
6,5W - 24VDC



VIRTUS T
6,5W - 24VDC



SLIM T6
6W - 24VDC



SLIM T10
10W - 24VDC